

# **30-Gallon** Air Compressors

Two Stage – Diesel



This two stage diesel-powered air compressor provides consistent and reliable air power for industrial, automotive and service body applications.

### COMPRESSOR PUMP

- Cast iron compressor pump
- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

#### ENGINE

- Electric start battery, box and cables not included
- · Glow plug equipped for easy starting in cold temperatures

#### FRAME

- Powder coated ASME receiver tank
- 3/16-inch base plate to reduce vibration
- Powder coated two-piece belt guard
- · Removable base plate offers flexible installation

### COMPONENTS

- Regulator and two gauges for tank and outlet pressure
- ASME safety valves
- Tank drain valve

#### LIMITED WARRANTY

3 year engine

## CERTIFICATION

• ASME Boiler and Pressure Vessel Code - UM



# **30-Gallon** Air Compressors – Two Stage – Diesel

MODEL NUMBER	CFM @ PSI*	HORSEPOWER/ENGINE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
ABS-9KD-30H	29.0 @ 175	9.1 HP Kohler KD440 OHV	Cable throttle	38x23x46.5in.	540 lb.	483 lb.
*Equipped with 150-PSI n	naximum rated regulator.					
ACCESSORY:						
PART NUMBER	DESCRIPTION				FITS MODEL	
AW-6000-1002	Equipment cover – Keeps your equipment clean, dry and looking like new				ABS-9KD-30H	
OPTIONS:						
PART NUMBER	DESCRIPTION				FITS I	MODEL
AX-0079	Battery box, cables and tray – Attaches to engine side of unit				ABS-9KD-30H	
IX-0001	Vibration isolator pads - Recommended for models mounted in service truck applications. Isolators protect the unit from vibration during use.				ABS-9KD-30H	

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.