

# **Portable Gasoline**

Dealer Hot Water Pressure Washers







This powerful pressure washer series is built to blast away the toughest grease and grime. It features a 12V Beckett burner, bottom-fired heat exchanger and pneumatic tires.

#### PUMP

- Adjustable stainless-steel and brass unloader valve
- Forged brass manifold
- Thermal relief valve

#### **ENGINE**

- Performance-proven OHV engine with low-oil protection
- 12V electric start battery not included

# FRAME

- Reinforced powder coated steel frame with center balanced lifting hook
- · 15-inch pneumatic tires

#### COMPONENTS

- ½-inch schedule 80 pipe coil with 4-pancake bottom-fired heat exchanger
- 12V Beckett burner
- No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel)
- · Adjustable temperature
- Hour meter

#### **MISCELLANEOUS**

- Temperature rise 130°F/54°C above ambient
- Water output temperature is 250°F in "wet" steam

# UNIT INCLUDES

- Quick connect nozzles 0°, 15°, 25° and 40°
- 1/4-inch MEG and 1/4-inch MQC wet steam nozzle 25°
- 50-foot x %-inch steel wire-braided high pressure hose
- Adjustable pressure insulated dual lance
- Professional-grade insulated trigger gun with safety lock-off
- External downstream detergent injector with detergent nozzle

### LIMITED WARRANTY

• 3 year engine



**Exclusive** 

**Dealer**Product

# Portable Gasoline

# Hot Water - DHG Series - Direct/Belt Drive

| DIRECT DRIVE MO | ODELS | ;   |                        |         |                       |                              |                         |                 |                       |          |         |
|-----------------|-------|-----|------------------------|---------|-----------------------|------------------------------|-------------------------|-----------------|-----------------------|----------|---------|
| MODEL NUMBER    | PSI   | GPM | DISPLACEMENT/ENGINE    | PUMP    | FUEL TANK<br>CAPACITY | BURNER FUEL<br>TANK CAPACITY | BURNER FUEL CONSUMPTION | BTU PER<br>HOUR | DIMENSIONS<br>(LxWxH) | SHIP WT. | NET WT. |
| DHG-4004-D0H6G  | 4000  | 3.7 | 389cc Honda GX390 OHV+ | General | 1.61 gallons          | 10.0 gallons                 | 2.14 gph                | 299,600         | 49.5x30x48in.         | 601 lb.  | 478 lb. |
| DHG-4004-D0V6G  | 4000  | 3.7 | 408cc Vanguard OHV     | General | 1.52 gallons          | 10.0 gallons                 | 2.14 gph                | 299,600         | 49.5x30x48in.         | 596 lb.  | 466 lb. |

### BELT DRIVE MODELS

| MODEL NUMBER   | PSI  | GPM | DISPLACEMENT/ENGINE    | PUMP    | CAPACITY     | TANK CAP.    | CONS.    | HOUR    | (LxWxH)       | WT.     | WT.     |
|----------------|------|-----|------------------------|---------|--------------|--------------|----------|---------|---------------|---------|---------|
| DHG-4004-B0H6G | 4000 | 3.7 | 389cc Honda GX390 OHV+ | General | 1.61 gallons | 10.0 gallons | 2.14 gph | 299,600 | 49.5x30x48in. | 643 lb. | 520 lb. |
| DHG-4004-B0V6G | 4000 | 3.7 | 408cc Vanguard OHV     | General | 1.52 gallons | 10.0 gallons | 2.14 gph | 299,600 | 49.5x30x48in. | 641 lb. | 511 lb. |

<sup>+49</sup> state engine. Not for sale in California.

#### ACCESSORIES:

| PART NUMBER  | DESCRIPTION  | FITS MODELS |
|--------------|--|-------------|
| 50-0195      | Hose reel – 13-inch, 150-foot maximum hose length  | All models  |
| 50-0196      | Hose reel – 16-inch, 200-foot maximum hose length  | All models  |
| AW-6000-1006 | Hot water equipment cover – Keeps your equipment clean, dry and looking like new; made from 600-denier vinyl-back polyester, water resistant, drawstrings to secure cover; Mi-T-M logo | All models  |
| AW-6000-1007 | Hot water equipment cover – Keeps your equipment clean, dry and looking like new; made from 600-denier vinyl-back polyester, water resistant, drawstrings to secure cover; no logo     | All models  |

#### OPTIONS:

| PART NUMBER | DESCRIPTION  | FITS MODELS |
|-------------|--|-------------|
| HX-0273     | Stainless-steel coil wrap – Converts powder coated painted coil wrap to stainless-steel material | All models  |
| HX-0278     | Skid feet – Stationary applications  | All models  |

