

HHB Series — Belt Drive



HHB-2503-0E2A

Tackle tough grease, grime and stubborn stains with the portable HHB Series. This series features an open drip-proof motor and stainless-steel coil wrap heat exchanger.

PUMP

- Adjustable high pressure detergent injector
- Factory preset unloader

MOTOR

- Open drip-proof electric motor with manual thermal overload protection
- 35-foot power cord

FRAME

- Powder coated steel frame assembly
- 13-inch flat-free tires

COMPONENTS

- Stainless-steel coil wrap with horizontal schedule 80 pip coil
- No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel)
- Racor fuel filter/water separator
- Adjustable thermostat
- Polyethylene float tank with inlet filter screen
- 10-gallon polyethylene fuel tank

MISCELLANEOUS

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25°, 40° and low pressure nozzle (except on HHB-303-0E1A)
- 50-foot x 3/8-inch high pressure hose (50-foot steam hose on HHB-303-0E1A)
- Adjustable pressure insulated dual lance (except on HHB-303-0E1A)
- Single lance with dual insulated grips; steam nozzle (HHB-303-0E1A)
- Professional-grade insulated trigger gun with safety lock-off

LIMITED WARRANTY

- 1 year electric motor

CERTIFICATION

- CSA Certified – US and Canada



Portable Electric

Hot Water – HHB Series – Belt Drive

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	PLUG TYPE	BURNER FUEL TANK CAPACITY	BURNER FUEL CONSUMPTION	BTU PER HOUR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
HHB-1002-0E1A	1000	2.0	1.5 HP, 115V, 1Ø, 16.2A	AR	NEMA 5-20P	10.0 gallons	1.23 gph	172,200	57x30x41.5in.	606 lb.	486 lb.
HHB-1003-0E1A	1000	2.8	2.0 HP, 115V, 1Ø, 20.0A	AR	NEMA 5-20P	10.0 gallons	1.84 gph	257,600	57x30x41.5in.	610 lb.	490 lb.
HHB-1502-0E1A	1500	1.8	2.0 HP, 115V, 1Ø, 19.9A	AR	NEMA 5-20P	10.0 gallons	1.23 gph	172,200	57x30x41.5in.	610 lb.	490 lb.
HHB-2503-0E2A	2500	2.8	6.0 HP, 230V, 1Ø, 28.0A	AR	NEMA 6-30P	10.0 gallons	1.84 gph	257,600	57x30x41.5in.	650 lb.	540 lb.
HHB-303-0E1A [^]	300	2.5	1.5 HP, 115V, 1Ø, 12.5A	AR	NEMA 5-15P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	480 lb.	460 lb.

[^]Steam unit.



NEMA 5-15P,
15-amp plug



NEMA 5-20P,
20-amp plug



NEMA 6-30P,
30-amp plug



HHB-2503-0E2A

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.